

ENTRY HANDLESETS

DOREX SERIES

T400 SERIES





SPECIFICATIONS

Certifications • 25 Year limited mechanical warranty

• 5 Year limited finish warranty

Door Thickness • 1¾-2¼" (44.5-57 mm)

Handing • Non handed

Backset • 2% - 2% (60–70 mm), adjustable

Spring Latch • Solid zinc alloy

• ½" (12.7 mm) throw

Deadbolt • Steel deadbolt with hardened steel security pin

•1" (25.4 mm) throw

Faceplate • 4-Way type (W), square corner;

convertible to drive-in

• 1 x 2 1/4" (25.4 x 57 mm)

Strike • Full-lip strike, round corner

13/4 x 21/4" (44.5 x 57 mm)

• Deadbolt strike, round corner

11/8 x 23/4" (29 x 70 mm)

Exterior Trim • Zinc die-cast handle

Interior Trim • Standard lever, square rose

Square thumb-turn trim

• Round trim and rose available

Mounting • Concealed mounting screws

• All mounting hardware included

Preparation • Cross bore: 21/8" (54 mm)

• Edge bore: 1" (25.4 mm)

• Plato: 5½" (140 mm) center-to-center

Cylinder • 5-pin cylinder

Weiser keyway

2 keys

Functions • Entry


Finish See Selection Guide.

T401	PL	LTS	C15	KD	W
SERIES	STYLE	TRIM	FINISH	KEYING	LATCH

SELECTION GUIDE

		C10B OIL RUB. BRONZE	C11P ANTIQUE BRONZE	C15 SATIN NICKEL	C15A ANTIQUE NICKEL	C19 MATTE BLACK	C26 POLISHED CHROME	C26D SATIN CHROME	C3 POLISHED BRASS	C32D SATIN S.STEEL	C4 SATIN BRASS	C5 ANTIQUE BRASS	V3* POLISHED BRASS	/CASE
ARCO	AR			•		•	•	•						6
PLATO	PL			•		•	•	•						6

OTHER FINISHES AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED – PLEASE CONTACT (*) LIFETIME FINISH WARRANTY



	Α	В	С
ARCO	211/16	5*	811/16
AR LTS	(68)	(127)	(220)
PLATO	211/16	51/2	927/32
PLLTS	(68)	(140)	(250)